

What is Claimed Is:

1. A tamper indicating device comprising:

a backing having a first side and a second side, wherein the backing comprises a first phase and a second phase, wherein the backing has a first level of light diffusion, and
5 when a peeling force is applied to the backing, the backing fractures and has a second level of light diffusion that is a higher level of light diffusion than the first level of light diffusion;

a flood coat applied to the second side of the backing, the flood coat defining a window therein; and

10 a mask applied to the tamper indicating device, the mask being in partial or whole registration with the window in the flood coat.

2. The tamper indicating device of claim 1, wherein the tamper indicating device further comprises at least one security marking applied to the first side of the
15 backing, wherein the security marking has substantially the same color as the flood coat.

3. The tamper indicating device of claim 1, further comprising an adhesive layer bonded to the flood coat.

20 4. The tamper indicating device of claim 3, wherein the adhesive layer is a pressure sensitive adhesive layer, and wherein the tamper indicating device further comprises a release liner applied to the pressure sensitive adhesive layer.

25 5. The tamper indicating device of claim 2, wherein security markings are colored the same color as the color of the flood coat.

6. An article including a tamper indicating device, comprising:
an object;
secured information;

30 a tamper indicating device, comprising:

a backing having a first side and a second side, wherein the backing

comprises a first phase and a second phase, wherein the backing has a first level of light diffusion, and when a peeling force is applied to the backing, the backing fractures and has a second level of light diffusion that is a higher level of light diffusion than the first level of light diffusion;

- 5 a flood coat applied to the second side of the backing; and
 a mask applied to the tamper indicating device, such that the mask obscures the secured information; and
 an adhesive layer attaching the tamper indicating device to the object.

10 7. The article of claim 6, wherein the flood coat defines a window.

8. The article of claim 6, wherein the tamper indicating device further comprises at least one security marking applied to the first side of the backing, wherein the security marking has substantially the same color as the flood coat.

15 9. The article of claim 8, wherein security markings are colored the same color as the color of the flood coat.

20 10. The article of claim 6, wherein the adhesive layer is bonded to the flood coat.

11. The article of claim 10, wherein the adhesive layer is a pressure sensitive adhesive layer, and wherein the tamper indicating device further comprises a release liner applied to the pressure sensitive adhesive layer.

25 12. An article, comprising:
 an object;
 secured information;
 a tamper indicating backing having a first side and a second side, wherein the
30 backing comprises a first phase and a second phase, wherein the backing is light transmissive, and wherein a peeling force causes the backing to fracture and become more

opaque;

an adhesive layer applied to the second side of the backing, wherein the adhesive layer is colored, and wherein the adhesive layer is bonded to the application surface of the object; and

5 a mask applied to the tamper indicating device, wherein the mask obscures the secured information.

13. The article of claim 12, wherein the tamper indicating device further comprises at least one security marking applied to the first side of the backing.

10

14. The article of claim 13 further comprising a flood coat applied to the second side of the backing, the flood coat defining a window therein, wherein security markings have substantially the same color as the color of the flood coat.

15 15. The article of claim 12, wherein the adhesive layer is a pressure sensitive adhesive layer, and wherein the tamper indicating device further comprises a release liner applied to the pressure sensitive adhesive layer.

16. A tamper indicating device comprising:

20 a backing having a first side and a second side, wherein the backing comprises a first phase and a second phase, wherein the backing has a first level of light diffusion, and when a peeling force is applied to the backing, the backing internally delaminates and has a second level of light diffusion that is a higher level of light diffusion than the first level of light diffusion;

25 a flood coat applied to the second side of the backing, the flood coat defining a window therein; and

a mask applied to the tamper indicating device, the mask being in partial or whole registration with the window in the flood coat.

30 17. The tamper indicating device of claim 16, wherein the tamper indicating device further comprises at least one security marking applied to the first side of the

backing, wherein the security marking has substantially the same color as the flood coat.

18. The tamper indicating device of claim 16, further comprising an adhesive layer bonded to the flood coat.

5

19. The tamper indicating device of claim 18, wherein the adhesive layer is a pressure sensitive adhesive layer, and wherein the tamper indicating device further comprises a release liner applied to the pressure sensitive adhesive layer.

10

20. The tamper indicating device of claim 17, wherein security markings are colored the same color as the color of the flood coat.

21. An article including a tamper indicating device, comprising:
an object;

15

secured information;

a tamper indicating device, comprising:

a backing having a first side and a second side, wherein the backing comprises a first phase and a second phase, wherein the backing has a first level of light diffusion, and when a peeling force is applied to the backing, the backing internally delaminates and has a second level of light diffusion that is a higher level of light diffusion than the first level of light diffusion;

20

a flood coat applied to the second side of the backing; and

a mask applied to the tamper indicating device, such that the mask obscures the secured information; and

25

an adhesive layer attaching the tamper indicating device to the object.

22. The article of claim 21, wherein the flood coat defines a window.

23. The article of claim 21, wherein the tamper indicating device further comprises at least one security marking applied to the first side of the backing, wherein the security marking has substantially the same color as the flood coat.

30

24. The article of claim 23, wherein security markings are colored the same color as the color of the flood coat.

5 25. The article of claim 21, wherein the adhesive layer is bonded to the flood coat.

26. The article of claim 25, wherein the adhesive layer is a pressure sensitive adhesive layer, and wherein the tamper indicating device further comprises a release liner
10 applied to the pressure sensitive adhesive layer.